



Электросварная седелка - моноблок

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Со встроенной фрезой для врезки под давлением
- С ответной нижней частью
- Штыревой контакт 4 мм
- Индикатор сварки
- Длинный выход для сварки
- Заглушка с уплотнительным кольцом для герметизации
- *Совместима с Газ-Стоп тип GS

	d (mm)	d1 (mm)	code	SP	GP	weight (kg)	d2 (mm)	H (mm)	H1 (mm)	L (mm)	L1 (mm)	z (mm)
*	63	20	193 131 932	1	20	0,368	25	146	44	144	76	110
	63	25	193 131 933	1	20	0,393	25	146	44	144	76	110
*	63	32	193 131 934	1	20	0,376	25	146	44	144	76	110
*	90	20	193 131 952	1	12	0,494	32	198	61	162	76	115
	90	25	193 131 953	1	12	0,503	32	198	61	162	76	115
*	90	32	193 131 954	1	12	0,505	32	198	61	162	76	115
	90	63	193 131 957	1	10	0,667	32	198	61	162	76	115
*	110	20	193 131 962	1	9	0,560	32	208	71	162	76	115
	110	25	193 131 963	1	9	0,570	32	208	71	162	76	115
*	110	32	193 131 964	1	9	0,574	32	208	71	162	76	125
	110	63	193 131 967	1	8	0,684	32	208	71	162	100	160
*	125	20	193 131 972	1	6	0,562	32	216	79	162	76	120
	125	25	193 131 973	1	6	0,552	32	216	79	162	76	120
*	125	32	193 131 974	1	6	0,574	32	216	79	162	76	120
	125	63	193 131 977	1	6	0,704	32	216	79	162	76	120
*	160	20	193 131 992	1	6	0,631	32	233	96	162	76	120
	160	25	193 131 993	1	6	0,641	32	233	96	162	76	125
*	160	32	193 131 994	1	6	0,648	32	233	96	162	76	130
	160	63	193 131 997	1	6	0,794	32	233	96	162	100	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>