



Электросварная седелка - моноблок

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Со встроенной фрезой для врезки под давлением
- С ответной нижней частью
- Штыревой контакт 4 мм
- Индикатор сварки
- Длинный выход для сварки
- Заглушка с уплотнительным кольцом для герметизации

d (mm)	d1 (mm)	code	SP	weight (kg)	d2 (mm)	H (mm)	H1 (mm)	L (mm)	L1 (mm)	z (mm)
40	20	193 131 412	1	0,225	16	99	33	103	70	102
40	25	193 131 413	1	0,226	16	99	33	103	70	102
40	32	193 131 414	1	0,225	16	99	33	103	70	120
50	20	193 131 422	1	0,214	16	104	38	103	70	102
50	25	193 131 423	1	0,212	16	104	38	103	70	102
50	32	193 131 424	1	0,228	16	104	38	103	70	120
63	20	193 131 432	1	0,428	25	134	44	126	70	115
63	25	193 131 433	1	0,431	25	134	44	126	70	115
63	32	193 131 434	1	0,425	25	134	44	126	70	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>