



Переход 90° электросварной ПЭ / латунь (CW617N) наружная резьба

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Со встроенными фиксаторами
- Штыревой контакт 4 мм
- Индикатор сварки
- Поставляется в комплекте

d (mm)	R (inch)	code	SP	weight (kg)	d1 (mm)	L (mm)	s (mm)
20	½	720 100 756	1	0,240	31	96	30
25	¾	720 100 757	1	0,260	36	97	35
32	1	720 100 758	1	0,368	44	98	40
32	1 ¼	720 100 766	1	0,500	44	100	50
32	1 ½	720 100 767	1	0,562	44	100	60
40	1	720 100 771	1	0,511	54	107	50
40	1 ¼	720 100 759	1	0,534	54	109	50
40	1 ½	720 100 772	1	0,615	54	109	60
50	1	720 100 776	1	0,677	66	116	60
50	1 ¼	720 100 777	1	0,771	66	118	60
50	1 ½	720 100 760	1	0,734	66	118	60
63	1 ¼	720 100 782	1	1,040	81	128	70
63	1 ½	720 100 783	1	1,039	81	128	70
63	2	720 100 761	1	1,108	81	132	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>