




## Переход 90° электросварной ПЭ / латунь (CW617N) внутренняя резьба

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Со встроенными фиксаторами
- Штыревой контакт 4 мм
- Индикатор сварки
- Поставляется в комплекте



d (mm)	Rp (inch)	code	SP	weight (kg)	d1 (mm)	L (mm)	s (mm)
32	1	<b>720 100 258</b>	1	0,359	44	89	40
40	1 ¼	<b>720 100 259</b>	1	0,525	54	100	50
50	1 ½	<b>720 100 260</b>	1	0,825	66	109	60
63	1	<b>720 100 281</b>	1	1,420	81	123	70
63	1 ¼	<b>720 100 282</b>	1	1,391	81	123	70
63	1 ½	<b>720 100 283</b>	1	1,305	81	123	70
63	2	<b>720 100 261</b>	1	1,165	81	123	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>