




Переход электросварной d25-d63 со встроенными фиксаторами

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Штыревой контакт 4 мм
- Индикатор сварки



d (mm)	d2 (mm)	code	SP	weight (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)
25	20	753 901 639	1	0,051	35	74	34	34	6
32	20	753 901 640	1	0,056	44	79	33	36	10
32	25	753 901 641	1	0,062	44	79	33	36	10
40	20	753 901 644	1	0,069	54	88	33	39	15
40	25	753 901 645	1	0,084	54	88	33	39	15
40	32	753 901 646	1	0,095	54	88	33	39	13
50	32	753 901 651	1	0,124	66	96	35	43	18
50	40	753 901 652	1	0,119	66	96	39	43	14
63	32	753 901 656	1	0,158	81	105	35	48	23
63	40	753 901 657	1	0,176	81	105	39	48	19
63	50	753 901 658	1	0,176	81	105	43	48	15

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>