



## Переход электросварной ПЭ / латунь (CW617N) внутренняя резьба

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Со встроенными фиксаторами
- Штыревой контакт 4 мм
- Индикатор сварки
- Поставляется в комплекте

d	Rp	code	SP	weight	d1	L	s
(mm)	(inch)			(kg)	(mm)	(mm)	(mm)
32	1	<b>720 920 258</b>	1	0,306	44	108	40
40	1 ¼	<b>720 920 259</b>	1	0,496	54	118	50
50	1 ½	<b>720 920 260</b>	1	0,725	66	126	60
63	1	<b>720 920 281</b>	1	1,300	81	138	70
63	1 ¼	<b>720 920 282</b>	1	1,230	81	138	70
63	1 ½	<b>720 920 283</b>	1	1,134	81	138	70
63	2	<b>720 920 261</b>	1	1,057	81	138	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>