



## Тройник 90° редукционный, электросварной d110-d250

- Полиэтилен 100 SDR11
- Давление для газа 10 бар / воды 16 бар
- Штыревой контакт 4 мм
- Индикатор сварки
- Две зоны сварки

d (mm)	d2 (mm)	code	weight (kg)	d1 (mm)	L (mm)	L1 (mm)	z (mm)	z1 (mm)	H (mm)
110	90	<b>753 211 034</b>	1,652	140	255	72	56	245	80
125	90	<b>753 211 035</b>	2,242	156	255	75	53	245	80
160	63	<b>753 211 037</b>	5,660	200	493	90	127	176	65
160	90	<b>753 211 039</b>	5,508	200	492	90	158	188	79
160	110	<b>753 211 040</b>	5,157	200	491	90	158	195	85
200	90	<b>753 211 059</b>	9,012	250	595	104	194	215	81
200	110	<b>753 211 060</b>	12,400	250	600	104	194	218	84
200	160	<b>753 211 063</b>	12,400	250	595	104	194	236	101
225	90	<b>753 211 069</b>	13,100	280	666	112	217	226	80
225	110	<b>753 211 070</b>	13,100	280	670	112	217	235	85
225	160	<b>753 211 073</b>	13,600	280	667	112	217	255	105
250	110	<b>753 211 080</b>	11,660	310	709	123	220	245	85
250	160	<b>753 211 083</b>	17,070	310	711	123	220	264	101

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>